AMENDMENTS TO THE CLAIMS

Please amend the claims as follows.

- (Currently Amended) A method for storing [[a]] data set having an enabled probe identification component and an associated data component, comprising:
 - encountering a probe during execution of an instrumented program, wherein
 the probe is associated with a first enabled probe identification (EPID)
 and a second EPID and wherein the first EPID is associated with a first
 action and the second EPID is associated with a second action;
 - executing the first action upon encountering the probe to obtain first data and executing the second action to obtain second data:
 - obtaining data from an instrumented program using a probe;
 - associating the data with an enabled probe identification; and
 - storing the <u>first</u> data in the data set, and the first EPID in a first per-consumer buffer;
 - storing a first metadata and the first EPID in a first per-consumer metadata

 table, wherein the first metadata defines a layout of the first data stored
 in the first per-consumer buffer, and wherein the first per-consumer
 buffer and the first per-consumer metadata table are accessible by a first
 consumer.
 - storing the second data and the second EPID in a second per-consumer buffer;
 and
 - storing a second metadata and the second EPID in a second per-consumer

 metadata table, wherein the second metadata defines a layout of the
 second data stored in the second per-consumer buffer, and wherein the

Application No.: 10/713,612

second per-consumer buffer and the second per-consumer metadata table are accessible by a second consumer

wherein the enabled probe identification is stored in the enabled probe identification component and the data is stored in the associated data set component, and

wherein the enabled probe identification is associated with metadata defining a layout of the data obtained using the probe.

 (Currently Amended) The method of claim 1, further comprising: defining a tracing function wherein the tracing function comprises [[an]] the first action[f:1]

associating the action with the enabled probe identification; and associating the probe with the enabled probe identification.

- (Currently Amended) The method of claim 2, wherein the tracing function is defined by [[a]] the first consumer.
- (Currently Amended) The method of claim 3, wherein the <u>first enabled probe</u> identification <u>EPID</u> and the second <u>EPID</u> are [[is]] defined on a per-consumer basis.
- (Canceled)
- 6. (Canceled)
- 7. (Currently Amended) The method of claim 4, wherein the <u>first</u> metadata includes at least one selected from the group consisting of an action name <u>associated</u> with the <u>first action</u>, a module name, a data size, a data type, and an action function for the first action.
- 8. (Canceled)

Application No.: 10/713,612

- 9. (Canceled)
- 10. (Canceled)
- 11. (Canceled)
- 12. (Canceled)
- 13.(Currently Amended) A system for storing a <u>first</u> data set <u>and a second data set</u>, wherein the data set comprises an enabled probe identification component and a data component comprising:
 - a probe obtaining data from encountered during execution of an instrumented program;
 - a tracing framework associating the probe with [[an]] a first enabled probe identification (EPID) and a second EPID, wherein the first EPID is associated with a first action and the second EPID is associated with a second action, wherein executing the first action obtains a first data from the probe, and wherein executing the second action obtains a second data from the probe;
 - a <u>first per-consumer</u> buffer storing the <u>first</u> data set <u>comprising the first EPID</u>

 and the <u>first data</u>, wherein the data is stored in the data component and the <u>enabled</u> probe identification is stored in the <u>enabled</u> probe identification component; and
 - [[an]] a first EPID-Metadata table relating the first EPID enabled probe identification to a first metadata defining a layout of the first data obtained from the probe;
 - a second per-consumer buffer storing the second data set comprising the second EPID and the second data; and

Application No.: 10/713,612

a second EPID-Metadata table relating the second EPID to a second metadata defining a layout of the second data obtained from the probe.

- 14. (Currently Amended) The system of claim 13, further comprising:

 wherein a consumer defines[[ing an]] the first action, wherein the tracing framework assigns the first EPID enabled probe identification to the first action.
- 15. (Canceled)
- 16. (Currently Amended) The system of claim 14, wherein the <u>first</u> metadata includes at least one selected from the group consisting of an action name, a module name, a data size, a data type, and an action function.
- 17. (Currently Amended) The system of claim 14, wherein the <u>first</u> enabled probe identification is defined with respect to the consumer.
- 18. (Currently Amended) A system for storing a <u>first</u> data set <u>and a second data set</u>, wherein the data set comprises an enabled probe identification component and a data eomponent, comprising:
 - a probe obtaining data from encountered during execution of an instrumented program;
 - a tracing framework:
 - assigning [[an]] a first enabled probe identification (EPID) to [[an]] a first action;

assigning a second EPID to a second action; and

associating the probe with the <u>first EPID</u> enabled probe identification and the second EPID, wherein executing the first action obtains a <u>first data by the probe, and wherein executing the second action obtains a second data by the probe;</u>

Application No.: 10/713,612

- a <u>first</u> per-consumer buffer storing the <u>first</u> data set <u>comprising</u> the <u>first</u> data

 and the <u>first</u> <u>EPID</u>;, wherein the data is stored in the data component

 and the enabled probe identification in the enabled probe identification

 component; and
- a second per-consumer buffer storing the second data set comprising the second data and the second EPID;
- [[an]] <u>a first EPID-Metadata</u> table relating the <u>first EPID</u> enabled probe identification to <u>a first</u> metadata defining a layout of the <u>first</u> data obtained by the probe; <u>and</u>
- a second EPID-Metadata table relating the second EPID to a second metadata defining a layout of the second data obtained by the probe.
- wherein the enabled probe identification is assigned to the <u>first</u> action is defined by the <u>a first</u> consumer associated with the <u>first</u> per-consumer buffer, and
- wherein the second action is defined by a second consumer associated with the second per-consumer buffer.

19. (Canceled)

20. (Currently Amended) The system of claim 18, wherein the <u>first</u> metadata includes at least one selected from the group consisting of an action name, a module name, a data size, a data type, and an action function.